

Retro



Custom




Combinations

The retro is a modular downlight assembly that is designed for easy adaptability between inserts whilst maintaining the same installation method and overall aesthetic. The frames are available in a circular and square frames as well as plaster in and trimmed installation kits.

Each frame is designed to take 50mm engine insert that is typical with architectural lighting.

The internal modular element is removable allowing for the frame to be maintained in case of design updates or damage.

The cradle is able to tilt to 30 Degrees and rotate internally 355 Degrees to focus on the desired location.



Modular


Round



Recessed
Trim



Plaster In
Trimless



Tapered

Oval


Round

Snoot


The metalised reflector color finishes can adapt to the visual identity of the space and public areas.

Variations


Sqaure



Recessed
Trim



Plaster In
Trimless



Tapered

Sqaure

Snoot

Deeply recessed light source and pinhole designs in the form of tapered and snoot can hide the light source and make this product that blends into the ceiling as an invisible glare free light ftting which is suitable in residential and hospitality environments.

Endless

Round Recessed
RR

White Trim
TW



Black Trim
TB



White Trim
TW



Black Trim
TB



Round Plaster
RP

Tapered

Reflector Black
RB



Reflector White
RW



Reflector Gold
RG



Reflector Matt
RM



Oval

Reflector Black
RB



Reflector White
RW



Decorative Round Black
DRB



Decorative Round White
DRW



Additional Options
RM - **R**eflector **M**att
RG - **R**eflector **G**old

Round

Reflector Black
RB



Reflector White
RW



Decorative Oval Black
DOB



Decorative Oval White
DOW



Additional Options
RM - **R**eflector **M**att
RG - **R**eflector **G**old

Snoot

Black Black
BB



White White
WW



White Black
WB



Black Gold
BG



Additional Options
WM - **W**hite **M**att
WG - **W**hite **G**old
BM - **B**lack **M**att

ARCH - RETRO - RX - TW - RF - DF - ACC

- Product Family
- Shape
- Instalation Type
- Trim Finish
- Refelector Finish *
- Plate Finish *
- Accessory *

* If required

Accessories

HC - **H**oney**c**omb Louvre
FG - **F**rosted **G**lass
DIFF - **Diff**usser
ST - **St**ripped Glass
Additional finishes available upon request.

Possibilities

Sqaure Recessed
SR

White **T**rim
TW



Black **T**rim
TB





White **T**rim
TW



Black **T**rim
TB

Sqaure **P**laster
SP

Tapered


Reflector **B**lack
RB




Reflector **W**hite
RW



Reflector **G**old
RG



Reflector **M**att
RM



Sqaure

Reflector **B**lack
RB



Reflector **W**hite
RW



Decorative **R**ound **B**lack
DRB



Decorative **R**ound **W**hite
DRW

Additional Options
RM - **R**eflector **M**att
RG - **R**eflector **G**old

Snoot

Black **B**lack
BB



White **W**hite
WW



White **B**lack
WB



Black **G**old
BG



Additional Options
WM - **W**hite **M**att
WG - **W**hite **G**old
BM - **B**lack **M**att

ARCH - RETRO - SX - TW - RF - DF - ACC

- Product Family
- Shape
- Instalation Type
- Trim Finish
- Refelector Finish *
- Plate Finish *
- Accessory *

* If required

Accessories

HC - **H**oney**c**omb Louvre
FG - **F**rosted **G**lass
DIFF - **Diff**usser
ST - **St**ripped Glass

Additional finishes available upon request.

Sqaure

Tapered

ARCH-RETRO-SR-TW-RW
ARCH-RETRO-SR-TW-RM
ARCH-RETRO-SR-TW-RB
ARCH-RETRO-SR-TW-RG
ARCH-RETRO-SR-TB-RW
ARCH-RETRO-SR-TB-RM
ARCH-RETRO-SR-TB-RB
ARCH-RETRO-SR-TB-RG

ARCH-RETRO-SP-TW-RW
ARCH-RETRO-SP-TW-RM
ARCH-RETRO-SP-TW-RB
ARCH-RETRO-SP-TW-RG
ARCH-RETRO-SP-TB-RW
ARCH-RETRO-SP-TB-RM
ARCH-RETRO-SP-TB-RB
ARCH-RETRO-SP-TB-RG

Sqaure

ARCH-RETRO-SR-TW-RW-DSW
ARCH-RETRO-SR-TW-RM-DSW
ARCH-RETRO-SR-TW-RB-DSW
ARCH-RETRO-SR-TW-RG-DSW
ARCH-RETRO-SR-TB-RW-DSB
ARCH-RETRO-SR-TB-RM-DSB
ARCH-RETRO-SR-TB-RB -DSB
ARCH-RETRO-SR-TB-RG-DSB

ARCH-RETRO-RP-TW-RW-DSW
ARCH-RETRO-SP-TW-RM-DSW
ARCH-RETRO-SP-TW-RB-DSW
ARCH-RETRO-SP-TW-RG-DSW
ARCH-RETRO-SP-TB-RW-DSB
ARCH-RETRO-SP-TB-RM-DSB
ARCH-RETRO-SP-TB-RB-DSB
ARCH-RETRO-SP-TB-RG-DSB

Snoot

ARCH-RETRO-SR-TW-WM
ARCH-RETRO-SR-TW-WW
ARCH-RETRO-SR-TW-WB
ARCH-RETRO-SR-TW-WG
ARCH-RETRO-SR-TB-BM
ARCH-RETRO-SR-TB-BB
ARCH-RETRO-SR-TB-BG

ARCH-RETRO-SP-TW-WM
ARCH-RETRO-SP-TW-WW
ARCH-RETRO-SP-TW-WB
ARCH-RETRO-SP-TW-WG
ARCH-RETRO-SP-TB-BM
ARCH-RETRO-SP-TB-BB
ARCH-RETRO-SP-TB-BG

Round

Tapered

ARCH-RETRO-RR-TW-RW
ARCH-RETRO-RR-TW-RM
ARCH-RETRO-RR-TW-RB
ARCH-RETRO-RR-TW-RG
ARCH-RETRO-RR-TB-RW
ARCH-RETRO-RR-TB-RM
ARCH-RETRO-RR-TB-RB
ARCH-RETRO-RR-TB-RG

ARCH-RETRO-RP-TW-RW
ARCH-RETRO-RP-TW-RM
ARCH-RETRO-RP-TW-RB
ARCH-RETRO-RP-TW-RG
ARCH-RETRO-RP-TB-RW
ARCH-RETRO-RP-TB-RM
ARCH-RETRO-RP-TB-RB
ARCH-RETRO-RP-TB-RG

Oval

ARCH-RETRO-RR-TW-RW-DOW
ARCH-RETRO-RR-TW-RM-DOW
ARCH-RETRO-RR-TW-RB-DOW
ARCH-RETRO-RR-TW-RG-DOW
ARCH-RETRO-RR-TB-RW-DOB
ARCH-RETRO-RR-TB-RM-DOB
ARCH-RETRO-RR-TB-RB -DOB
ARCH-RETRO-RR-TB-RG-DOB

ARCH-RETRO-RP-TW-RW-DOW
ARCH-RETRO-RP-TW-RM-DOW
ARCH-RETRO-RP-TW-RB-DOW
ARCH-RETRO-RP-TW-RG-DOW
ARCH-RETRO-RP-TB-RW-DOB
ARCH-RETRO-RP-TB-RM-DOB
ARCH-RETRO-RP-TB-RB-DOB
ARCH-RETRO-RP-TB-RG-DOB

Round


ARCH-RETRO-RR-TW-RW-DRW
ARCH-RETRO-RR-TW-RM-DRW
ARCH-RETRO-RR-TW-RB-DRW
ARCH-RETRO-RR-TW-RG-DRW
ARCH-RETRO-RR-TB-RW-DRB
ARCH-RETRO-RR-TB-RM-DRB
ARCH-RETRO-RR-TB-RB -DRB
ARCH-RETRO-RR-TB-RG-DRB

ARCH-RETRO-RP-TW-RW-DRW
ARCH-RETRO-RP-TW-RM-DRW
ARCH-RETRO-RP-TW-RB-DRW
ARCH-RETRO-RP-TW-RG-DRW
ARCH-RETRO-RP-TB-RW-DRB
ARCH-RETRO-RP-TB-RM-DRB
ARCH-RETRO-RP-TB-RB-DRB
ARCH-RETRO-RP-TB-RG-DRB


Snoot

ARCH-RETRO-RR-TW-WM
ARCH-RETRO-RR-TW-WW
ARCH-RETRO-RR-TW-WB
ARCH-RETRO-RR-TW-WG
ARCH-RETRO-RR-TB-BM
ARCH-RETRO-RR-TB-BB
ARCH-RETRO-RR-TB-BG

ARCH-RETRO-RP-TW-WM
ARCH-RETRO-RP-TW-WW
ARCH-RETRO-RP-TW-WB
ARCH-RETRO-RP-TW-WG
ARCH-RETRO-RP-TB-BM
ARCH-RETRO-RP-TB-BB
ARCH-RETRO-RP-TB-BG



Retro+Engine



Powerful Pair

The retro fitting is combined with our engines to provide the complete lighting solution.

Once frame is installed in ceiling, LED module and power supply can be approached from the front side, without dismounting luminaire from the ceiling. This makes the up-grade of the light source and maintenance very easy and effective.







There are 4 engines ranges available that are part of the archlum range.



Swivelling of light source up to 30° and rotation for 355° allows to direct light beam towards objects and artworks and their accentuation by means of spot light distribution.


Wide beam angle illuminating wall surface can be used for generating vertical illumination and increase portion of general light, providing spatial and open feeling.

Miera Engine

Superspot 14°
Narrow 30°

Engine

Superspot 10°
Narrow 13°
Medium 24°
Wide 38°
Flood 60°




The right light for the right space

Engine IP


Narrow 15°
Medium 24°
Wide 35°
Flood 60°


Engine Vario


Narrow 17° -
Wide 53°












logo

Meira Engine





Bartenbach
TECHNOLOGY INSIDE

State of the art Downlight

Intergrating the miera engine into the retro downlight is the ideal combination for downlights that are able to make an impact such as large hospitality atriums. The engine comes in high and medium output options.


The Meira family features a unique, state-of-the-art reflector developed by Bartenbach — crafted in Austria to the highest optical standards.

Optimised for superior cut-off through its carefully calculated height ratio, the Meira reflector offers a minimal difference between the main beam angle and the field angle.

This results in a sharp cut-off and enhanced visual comfort compared to standard reflector solutions, while also delivering strong contrast and a dramatic lighting effect where required.

Its microfacet design ensures precise control of LED light output, achieving excellent uniformity with no colour shift across angles.


With a compact diameter and discreet form, Meira combines refined aesthetics with the latest high-density COB technology — making it a premium choice for sophisticated lighting design.



Meira Superspot



Meira Narrow




Meira Engine


Bartenbach
TECHNO LOGY INSIDE

archlum


Meira Engine
Narrow







Miera Max Narrow - 30 Degrees



5 YEARS WARRANTY | IP20 | CE | **CRI 95** | **UGR < 16** | **30°**

Catalogue ID	CCT	Power (W)	Light Output	Dimensions
ARCH-MEIRAM-X-30-922-7-Y	2200K	6.8W	650 lm	ø50x73 mm
ARCH-MEIRAM-X-30-927-7-Y	2700K		680 lm	
ARCH-MEIRAM-X-30-930-7-Y	3000K		700 lm	
ARCH-MEIRAM-X-30-940-7-Y	4000K		750 lm	


ARCH - MIERA - X - 30 - 927 - 14 - Y — Finishes

- Product Family
- Installation Type
- Beam Angle
- Wattage
- Colour Temperature
- CRI

X = Installation Method

I = Insert





Shape
ø50x73 mm

Finishes
Ral 9003 , RAL 9001 (plus more)


Colour Temperature
2200K , 2700K, 3000K, 4000K

Beam Angle
30°

Control
Phase
DALI
0-10
Bluetooth

Driver ordered seperately

Installation Methods





Bartenbach
TECHNO LOGY INSIDE

archlum


Meira Engine
Superspot







Miera Max Superspot - 14 Degrees



5 YEARS WARRANTY | IP20 | Ø52mm | CE

CRI 95 **UGR < 16** **14°**

Catalogue ID	CCT	Power (W)	Light Output	Dimensions
ARCH-MEIRAM-X-14-922-7-Y	2200K	6.8W	650 lm	ø58x73 mm
ARCH-MEIRAM-X-14-927-7-Y	2700K		680 lm	
ARCH-MEIRAM-X-14-930-7-Y	3000K		700 lm	
ARCH-MEIRAM-X-14-940-7-Y	4000K		750 lm	

ARCH - MIERA - X - 14 - 927 - 14 - Y — Finishes


- Product Family
- Installation Type
- Beam Angle
- CRI
- Colour Temperature
- Wattage

X = Installation Method

I = Insert

archlum





Shape
ø50x73 mm

Finishes
Ral 9003 , RAL 9001 (plus more)


Colour Temperature
2200K , 2700K, 3000K, 4000K


Beam Angle
30°

Control
Phase
DALI
0-10
Bluetooth

Driver ordered seperately


Installation Methods





Engine











The engine is a replacement of 50 W MR16 halogen lamps or 20 W HID lamp.


With three different beam angles, Spot, Medium and Wide archlum's MR16 LED engine can be used in various applications ranging from accent illumination of sculptures and artworks, to general illumination in indoor areas.


Available if warm light colors, it is suitable for use in high class hotels and restaurants. With a color rendering index of max. CRI 97 and R9(red)>85, colour reproduction of our MR16 is close to that of sunlight.

Deep TRI lens is optimised for best light control, whiles faceted structure is spreading light over large surface to maximise visual comfort.


13°


24°


38°


60°

Beam me up

Large volumetric TIR lens has specific relation of diameter and height, which allows better control of light in comparison to the flat Fresnel lenses.
This increase culmination ability of the lens and gives it more precise light beam.


Dark lens holder is absorbing any light that might escaping lens, instead of reflecting it back without control as a glary, stray light.

Because of contact between reflecting and refracting (exit) surface, lens rim is area especially critical for generating uncontrolled stray light. By covering this area with a dark snoot we are precisely eliminating stray light, without major influence on the optic efficiency.



archlum





Thermal Management

Dense heat sink fins, or incorrect positioning can block the airflow and lead to air pockets where hot air is accumulated and cannot be extracted from the heat sink.

Designed by our R&D team this heat sink has optimised fins size and fin distance to promote air-flow and allows best usage of heat sing volume and surface area.

This allow us to dissipate more heat from this only 70mm high engine.

Engine

archlum


Engine
Narrow







Engine Narrow



5 YEARS WARRANTY | IP20 | CE | **CRI 95** | **UGR < 16** | **13°**

Catalogue ID	CCT	Power (W)	Light Output	Dimensions
ARCH-MEIRAM-X-30-922-7-Y	2200K	6.8W	650 lm	ø50x70 mm
ARCH-MEIRAM-X-30-927-7-Y	2700K		680 lm	
ARCH-MEIRAM-X-30-930-7-Y	3000K		700 lm	
ARCH-MEIRAM-X-30-940-7-Y	4000K		750 lm	

ARCH - MIERA - X - 30 - 927 - 14 - Y — Finishes


- Product Family
- Installation Type
- Beam Angle
- CRI
- Colour Temperature
- Wattage

X = Installation Method

I - Insert

archlum





Shape
ø50x70 mm

Finishes
Ral 9003 , RAL 9001 (plus more)

Colour Temperature
2200K , 2700K, 3000K, 4000K

Beam Angle
13°

Control
Phase
DALI
0-10
Bluetooth

Driver ordered seperately

Installation Methods



archlum


Engine
Medium







Engine Medium



5 YEARS WARRANTY | IP20 | CE | **CRI 95** | **UGR < 16** | **24°**

Catalogue ID	CCT	Power (W)	Light Output	Dimensions
ARCH-MEIRAM-X-30-922-7-Y	2200K	6.8W	650 lm	ø58x73 mm
ARCH-MEIRAM-X-30-927-7-Y	2700K		680 lm	
ARCH-MEIRAM-X-30-930-7-Y	3000K		700 lm	
ARCH-MEIRAM-X-30-940-7-Y	4000K		750 lm	


ARCH - MIERA - X - 30 - 927 - 14 - Y — Finishes

- Product Family
- Installation Type
- Beam Angle
- CRI
- Colour Temperature
- Wattage

X = Installation Method

I - Insert





Shape
ø50x70 mm

Finishes
Ral 9003 , RAL 9001 (plus more)

Colour Temperature
2200K , 2700K, 3000K, 4000K

Beam Angle
24°

Control
Phase
DALI
0-10
Bluetooth

Driver ordered seperately

Installation Methods



archlum


Engine Wide







Engine Wide



5 YEARS WARRANTY | IP20 | Ø52mm | CE

CRI 95 **UGR < 16** **38°**

Catalogue ID	CCT	Power (W)	Light Output	Dimensions
ARCH-MEIRAM-X-30-922-7-Y	2200K	6.8W	650 lm	ø58x73 mm
ARCH-MEIRAM-X-30-927-7-Y	2700K		680 lm	
ARCH-MEIRAM-X-30-930-7-Y	3000K		700 lm	
ARCH-MEIRAM-X-30-940-7-Y	4000K		750 lm	


ARCH - MIERA - X - 30 - 927 - 14 - Y — Finishes

- Product Family
- Installation Type
- Beam Angle
- CRI
- Colour Temperature
- Wattage

X = Installation Method

I - Insert





Shape
ø50x70 mm

Finishes
Ral 9003 , RAL 9001 (plus more)

Colour Temperature
2200K , 2700K, 3000K, 4000K

Beam Angle
38°

Control
Phase
DALI
0-10
Bluetooth

Driver ordered seperately


Installation Methods





Engine IP








Beam me up

Engine IP has all the features of the original engine and encorpartes an IP rated gland and silicone fixings making it perfect for wet environments such as bathrooms and exterior.

This ensure consistency within multiple zones such as bedrooms and bathrooms combined.

The focusing element within the retro downlight allows for the light to be directed to reflective surfaces such as the bathroom sink.





Engine IP

archlum


Engine IP
Narrow







Engine IP - Narrow



5 YEARS WARRANTY | IP65 | CE | **CRI 95** | **UGR < 16** | **15°**

Catalogue ID	CCT	Power (W)	Light Output	Dimensions
ARCH-MEIRAM-X-30-922-7-Y	2200K	6.8W	650 lm	ø50x70 mm
ARCH-MEIRAM-X-30-927-7-Y	2700K		680 lm	
ARCH-MEIRAM-X-30-930-7-Y	3000K		700 lm	
ARCH-MEIRAM-X-30-940-7-Y	4000K		750 lm	

ARCH - MIERA - X - 30 - 927 - 14 - Y — Finishes


- Product Family
- Installation Type
- Beam Angle
- CRI
- Colour Temperature
- Wattage

X = Installation Method

I - Insert

archlum





Shape
ø50x70 mm

Finishes
Ral 9003 , RAL 9001 (plus more)


Colour Temperature
2200K , 2700K, 3000K, 4000K

Beam Angle
15°

Control
Phase
DALI
0-10
Bluetooth

Driver ordered seperately


Installation Methods




archlum


Engine IP
Medium







Engine IP - Medium



5 YEARS WARRANTY | IP65 | CE | **CRI 95** | **UGR < 16** | **24°**

Catalogue ID	CCT	Power (W)	Light Output	Dimensions
ARCH-MEIRAM-X-30-922-7-Y	2200K	6.8W	650 lm	ø50x70 mm
ARCH-MEIRAM-X-30-927-7-Y	2700K		680 lm	
ARCH-MEIRAM-X-30-930-7-Y	3000K		700 lm	
ARCH-MEIRAM-X-30-940-7-Y	4000K		750 lm	


ARCH - MIERA - X - 30 - 927 - 14 - Y — Finishes

- Product Family
- Installation Type
- Beam Angle
- CRI
- Colour Temperature
- Wattage

X = Installation Method

I - Insert





Shape
ø50x70 mm

Finishes
Ral 9003 , RAL 9001 (plus more)


Colour Temperature
2200K , 2700K, 3000K, 4000K

Beam Angle
24°

Control
Phase
DALI
0-10
Bluetooth

Driver ordered seperately


Installation Methods




archlum


Engine IP
Wide







Engine IP - Wide



5 YEARS WARRANTY | IP65 | CE | **CRI 95** | **UGR < 16** | **35°**

Catalogue ID	CCT	Power (W)	Light Output	Dimensions
ARCH-MEIRAM-X-30-922-7-Y	2200K	6.8W	650 lm	ø50x70 mm
ARCH-MEIRAM-X-30-927-7-Y	2700K		680 lm	
ARCH-MEIRAM-X-30-930-7-Y	3000K		700 lm	
ARCH-MEIRAM-X-30-940-7-Y	4000K		750 lm	

ARCH - MIERA - X - 30 - 927 - 14 - Y — Finishes


- Product Family
- Installation Type
- Beam Angle
- Wattage
- CRI
- Colour Temperature

X = Installation Method

I - Insert

archlum





Shape
ø50x70 mm

Finishes
Ral 9003 , RAL 9001 (plus more)


Colour Temperature
2200K , 2700K, 3000K, 4000K

Beam Angle
35°

Control
Phase
DALI
0-10
Bluetooth

Driver ordered seperately


Installation Methods




archlum


Engine IP
Flood







Engine IP - Flood



5 YEARS WARRANTY | IP65 | CE | **CRI 95** | **UGR < 16** | **60°**

Catalogue ID	CCT	Power (W)	Light Output	Dimensions
ARCH-MEIRAM-X-30-922-7-Y	2200K	6.8W	650 lm	ø50x70 mm
ARCH-MEIRAM-X-30-927-7-Y	2700K		680 lm	
ARCH-MEIRAM-X-30-930-7-Y	3000K		700 lm	
ARCH-MEIRAM-X-30-940-7-Y	4000K		750 lm	

ARCH - MIERA - X - 30 - 927 - 14 - Y — Finishes


- Product Family
- Installation Type
- Beam Angle
- CRI
- Colour Temperature
- Wattage

X = Installation Method

I - Insert

archlum





Shape
ø50x70 mm

Finishes
Ral 9003 , RAL 9001 (plus more)


Colour Temperature
2200K , 2700K, 3000K, 4000K

Beam Angle
60°

Control
Phase
DALI
0-10
Bluetooth

Driver ordered seperately

Installation Methods






Vario Engine




Engine
Vario





Engine Vario



5 YEARS WARRANTY | IP20 | Ø52mm | CE

CRI 95 **UGR < 16** **17°- 53°**


Catalogue ID	CCT	Power (W)	Light Output	Dimensions
ARCH-MEIRAM-X-30-922-7-Y	2200K	6.8W	650 lm	ø50x70 mm
ARCH-MEIRAM-X-30-927-7-Y	2700K		680 lm	
ARCH-MEIRAM-X-30-930-7-Y	3000K		700 lm	
ARCH-MEIRAM-X-30-940-7-Y	4000K		750 lm	

ARCH - MIERA - X - 30 - 927 - 14 - Y — Finishes

- Product Family
- Installation Type
- Beam Angle
- CRI
- Colour Temperature
- Wattage

X = Installation Method

I - Insert



Shape
ø50x70 mm

Finishes
Ral 9003 , RAL 9001 (plus more)

Colour Temperature
2200K , 2700K, 3000K, 4000K

Beam Angle
17° - 53°

Control
Phase
DALI
0-10
Bluetooth

Driver ordered seperately

Installation Methods

